

Performance —

PF 1400M TN EP

Catering



Technical data

Gross volume	1380 lt
Working temperature	-2+8 °C
Motor type	Remote
Refrigerant	R452A
Cooling power	703 W (-10°C / +45°C)
Absorption	391 W
Voltage/Frequency	230V/1~/50Hz
Climate class	5 / (40°C 40%)

Capacity

Trays pitch	25
-------------	----

Energy data (UE Reg. 2015/1094)

Type	Unenforceable regulation
------	--------------------------

Refrigeration details

Refrigeration unit	Remote with possibility to get as optional protection cover
Evaporator	Cataphoresis-treated for high corrosion resistance and installed external to compartment in order to ensure bigger loading capacity
Defrost	Automatic by electric heater
Condensate evaporation	Automatic by electric heater

Construction details

Product dimensions WxDxH	1435x810x2080
Packaging dimensions WxDxH	1500x840x2190
Gross weight	170 Kg
Net weight	151 Kg
Structure	Stainless steel AISI 304 monocoque
External/Internal material	Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel
Insulation thickness	60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)
Inner corners	Rounded for an easy cleaning
Door	2 Self-closing doors with 105° door stop
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption
Feet	In AISI 304 stainless steel, height adjustable (90mm-125mm)

Functions

Control panel	Compact, simple and intuitive touch screen display
Open door alarm	Visual

Accessories

Lock	As standard
No. included accessories	6 - Plastic-coated grid GN 2/1 530x650 mm 6 - Pair of runners for grid 530x650 mm (Mod. 700/1400)

Remote unit data

Refrigerant gas for remote motor unit	Set up for R452A
---------------------------------------	------------------

Versions

Versions	Power supply frequency 60Hz
----------	-----------------------------