

Performance — PF 700M TN EP

Catering



Technical data

| | |
|---------------------|-----------------------|
| Gross volume | 630 lt |
| Working temperature | -2+8 °C |
| Motor type | Remote |
| Refrigerant | R452A |
| Cooling power | 482 W (-10°C / +45°C) |
| Absorption | 377 W |
| Voltage/Frequency | 230V/1~/50Hz |
| Climate class | 5 / (40°C 40%) |

Capacity

| | |
|-------------|----|
| Trays pitch | 25 |
|-------------|----|

Energy data (UE Reg. 2015/1094)

| | |
|------|--------------------------|
| Type | Unenforceable regulation |
|------|--------------------------|

Refrigeration details

| | |
|------------------------|---|
| Refrigeration unit | Remote with possibility to get as optional protection cover |
| Evaporator | Cataphoresis-treated for high corrosion resistance and installed external to compartment in order to ensure bigger loading capacity |
| Defrost | Automatic by electric heater |
| Condensate evaporation | Automatic by electric heater |

Construction details

| | |
|----------------------------|---|
| Product dimensions WxDxH | 702x810x2080 |
| Packaging dimensions WxDxH | 770x840x2190 |
| Gross weight | 106 Kg |
| Net weight | 92 Kg |
| Structure | Stainless steel AISI 304 monocoque |
| External/Internal material | Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel |
| Insulation thickness | 60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP) |
| Inner corners | Rounded for an easy cleaning |
| Door | 1 Self-closing door with 105° door stop. Right hinged, reversible on-site |
| Door gasket | Magnetic and removable, designed to improve insulation and to reduce energy consumption |
| Feet | In AISI 304 stainless steel, height adjustable (90mm-125mm) |

Functions

| | |
|-----------------|--|
| Control panel | Compact, simple and intuitive touch screen display |
| Open door alarm | Visual |

Accessories

| | |
|--------------------------|--|
| Lock | As standard |
| No. included accessories | 3 - Plastic-coated grid GN 2/1 530x650 mm 3 - Pair of runners for grid 530x650 mm (Mod. 700/1400) |

Remote unit data

| | |
|---------------------------------------|------------------|
| Refrigerant gas for remote motor unit | Set up for R452A |
|---------------------------------------|------------------|

Versions

| | |
|----------|-----------------------------|
| Versions | Power supply frequency 60Hz |
|----------|-----------------------------|